



LamGlide[®] Bushings

www.daytonlamina.com
Check our website for the latest technical information.



LamGlide[®] bushings can be used in many industry applications:

- ◆ Metal Stamping
- ◆ Transfer Machinery
- ◆ Special Machines
- ◆ Automation
- ◆ Farm Equipment
- ◆ Sports and Fitness Equipment
- ◆ Medical Equipment

LamGlide[®] bushings provide solutions to a number of engineering challenges:

- ◆ Ingests foreign particles
- ◆ Vibration dampening
- ◆ Compatible with most lubricants*
- ◆ High load, low speed applications
- ◆ Low moisture absorbency rate
- ◆ Can be operated without any added lubrication in certain cases

LamGlide[®] bushings have outstanding physical, mechanical and chemical properties:

- ◆ Self-aligning
- ◆ Tolerates edge loading
- ◆ Dimensional stability
- ◆ Chemical resistant
- ◆ Lightweight material


Restrictions:

- ◆ Maximum operating temperature of 482°
- ◆ I.D.s will be manufactured in accordance with Lamina's Class 3 tolerance grade unless otherwise specified.


** Not recommended for use with Molybdenum-based lubricants.*

APPLICATION DATA SHEET

Application Type (Choose one and give appropriate details)

Linear  Linear stroke seen by bushing = _____ inches or mm
 Maximum application speed = _____ cycles per minute
 Total press stroke or machine stroke = _____ inches or mm

Radial  Rpm = _____

Combination (Linear & Radial)  Linear stroke seen by bushing = _____ inches or mm
 plus
 Degrees of rotation seen by bushing = _____
 or
 Rpm = _____

Application Description

Stamping Die Mold Automation Equipment Machinery Marine
 Other (Specify) _____

I.D. (Nominal Inside Diameter) = _____ inches or mm

I.D. Tolerance =

Choose one tolerance scenario

- 0.0000
- + _____ inches or mm
- + _____ inches or mm
- + _____ inches or mm

If this LamGlide® bushing is replacing an existing conventional or self-lubricated bushing, state the manufacturer's name and part number and skip the remainder of this form. _____

or specify ANSI/ISO fit class ("g6," "H7," etc.) _____

O.D. (Nominal Outside Diameter) = _____ inches or mm

O.D. Tolerance =

Choose one tolerance scenario

- + 0.0000 **DEMOUNTABLE**
- _____ inches or mm
- _____ inches or mm
- _____ inches or mm

OR

- 0.0000 **PRESS-FIT**
- + _____ inches or mm
- + _____ inches or mm
- + _____ inches or mm

or specify ANSI/ISO fit class ("g6," "H7," etc.) _____

Nominal Length = _____ inches or mm

Length Tolerance = +/- _____ inches or mm

Guidepost / Mating Shaft Nominal Diameter = _____ inches or mm

Guidepost / Mating Shaft Tolerance =

Choose one tolerance scenario

- + 0.0000
- _____ inches or mm
- _____ inches or mm
- _____ inches or mm

or specify ANSI/ISO fit class ("g6," "H7," etc.) _____

Application Steady-State Operating Temperature (or Range of Temperatures) = _____ (°F or °C)
(Circle one)

Thrust Load (if known) = _____ lbf or kN Chemical Exposure (if any) _____
(Circle one)

Committed to Quality & Customer Satisfaction

We are a leading manufacturer of tool, die and mold components for the metal-working and plastics industries. As a customer focused, world-class supplier of choice, we provide the brands, product breadth, distribution network and technical support for all your metal forming needs.

We will help our customers to compete globally by providing innovative and value added products and services.

Distributed by:



Registered
to ISO 9001



Registered
to ISO 14001



Dayton Lamina Corporation
38505 Country Club Drive, Suite 100
Farmington Hills, MI USA 48331
Tel: 248-489-9122, 800-652-6462
Fax: 248-553-6842, 800-406-4410
E-Mail: info@anchorlamina.com
www.daytonlamina.com